



) EYE-LCD7000-HD

eyevis LCD Series

) DISPLAY CHARACTERISTICS

- ▶ Professional 70 inch LCD Monitor with S-PVA TFT-Display Panel
- ▶ Full HD Resolution (1920x1080px)
- ▶ 16:9 Aspect Ratio / Landscape or Portrait Installation
- ▶ Various Input Possibilities
- ▶ Metal Standard Chassis (standard black RAL9005, different RAL colours available on request)
- ▶ Different Installation Possibilities
- ▶ Optional with High Quality Speakers

) TECHNICAL SPECIFICATIONS

) LCD Panel

Technology	S-PVA LCD
Max. Image Resolution	1,920 x 1,080 (full HD)
Colours	16.7 Millionen (8bits-true)
Viewing Angle (H/V)	178° / 178°
Response Time	8 ms (Grey-to-Grey)
Contrast Ratio	1500:1
Brightness	600 cd/m ² (Typical)

) Connectors & Control

Inputs:	1 x Display Port up to 2560x1600 (60Hz), HDCP support 2 x HDMI 1.3, True High Definition 1080p, HDCP support 1 x RGB (15-pin H-DSUB female), captures up to 205MHz, Supports up to 1792x1344@60Hz or 1920x1260@60Hz or 1600x1200@75Hz standard modes 1 x Video Input, supports Composite Video, S-Video, and Component Video 1 x 3G-HD-SDI input (optional) 1 x RS232 Serial Port 1 x Audio In (L/R Cinch)
---------	--

) Power Supply

Input Voltage	100-250V 50/60Hz; Integrated Mains Adapter
Power Consumption	700 Watt (max. 1000 Watt)

) Environmental

Temperature	0-40°C (<50%RH)
Humidity	20-80%RH (T<40°C)

) Mechanical

Screen Diagonal	70" (ca. 177 cm)
Screen Area	1630 x 952 mm
Dimensions (WxHxD)	1677.6 x 999.6 x 148 mm
Weight	95 kg

) Options

Input Option:	3G-HD-SDI Input
Audio:	High Quality Speakers + integr. Amplifier
Touch:	Optical Touch Surface
Installations:	Different wallmounts and stands available



eyevis GmbH

Hundsschleestr. 23 • 72766 Reutlingen • Germany
 Phone: + 49 (0) 7121 43303 - 0 • Fax: + 49 (0) 7121 43303 - 22
 www.eyevis.de • info@eyevis.de
 As at: August 2010 • Subject to change!
 All trademarks and registered trademarks are the property of their respective owners. Copyright © 2010 eyevis GmbH. All rights reserved.